



Worldwide Foam
A Jacobs & Thompson Company

5220

EPDM

This data sheet property values are typical of the material and are intended to provide guidance to customers; they do not constitute a specification and should not be used for specification development.

Corporate Headquarters:

1806 Conant St.
Elkhart, IN 46516

www.worldwidefoam.com

Info@worldwidefoam.com

Ph: 574-968-8268

Fax: 574-970-0926



Item	Specs	Test Method
Grade	2A1	ASTM D1056-07
Density (PCF) (kg/m ³)	6.25 - 8.75 PCF 100 - 140 kg/m ³	ASTM D1056
Compression Deflection (CFD) (psi) (kPa) @25%	4.3 psi 30 kPa	ASTM D1056
Hardness - Durometer Shore OO	35– 50	ASTM D 2240
25% Compression Set %	30	ASTM D 1056
Tensile Strength (psi)(kPa)	43 psi 300 kPa	ASTM D412
Elongation (%)	80	ASTM D412
Tear Strength (lb/in)(kN/m)	6.9 lb/in 1.2 kN/m	ASTM D624

The data on this technical data sheet should be used as a guideline for product selection. This data is not intended to represent, replace or be used as a proxy for a specific product sales specification. The physical properties are averages based on limited production runs and are subject to change as additional data becomes available.