

August, 2016

## 3M™ Scrim Reinforced Adhesive Transfer Tape L1 + RT

### Product Description

The L1 adhesive platform features a modified acrylic adhesive with good initial tack and peel adhesion to many open cell foam substrates. The 3M L1 tapes are designed to withstand temperatures up to 200°F (93°C) and bond well to a wide range of foam substrates, including Polyurethane (PU) foam, Cross-Linked Polyethylene (PE) foam, and Microcellular Urethane foam. All L1 constructions feature a white 74# densified kraft (DK) liner for excellent processing.



### Product Features

- The L1 adhesive is a modified acrylic adhesive that withstands temperatures up to 200°F (93°C).
- Adhesive offers good initial tack and peel adhesion to many open cell foam materials.
- Bonds well to polyurethane (PU) foam, cross-linked polyethylene (PE) foam, and microcellular urethane foam.
- An 74# white colored, unprinted densified kraft (PCK) liner for excellent processing.

# 3M™ Scrim Reinforced Adhesive Transfer Tape L1 + RT

## Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

## Typical Physical Properties

Property	Values	
Adhesive Thickness	0.081 mm	3.2 mil
Liner	74# DK	
Liner Thickness	0.103 mm	4.1 mil
Liner Color	White	
Product Construction	L1+RT adhesive transfer tape is reinforced with a high density scrim carrier to boost dimensional stability during lamination processes. An adhesive coat weight of 3.2 mils allows the adhesive to flow and ensures good bond strength even around tight radiuses and contoured surfaces.	

## Typical Performance Characteristics

Property	Values	Method	Dwell/Cure Time	Test Condition	Notes
Static Shear	34 min	ASTM D3654	72 hr	1000 g @ Room Temperature	1 in <sup>2</sup> sample size
Static Shear	<1 min	ASTM D3654	72 hr	1000 g @ 70°C (158°F)	1 in <sup>2</sup> sample size

T-Peel Adhesion to Foam (Faceside)		Substrate	Failure mode
4.2 N/cm	22 oz/in	Polyurethane Foam	POF
3 N/cm	27 oz/in	Microcellular Urethane	POF
2.7 N/cm	25 oz/in	Cross-linked Polyethylene	FP

Property: T-Peel Adhesion to Foam (Faceside)

Method: ASTM D1876

Dwell/Cure Time: 72 hr @ Room Temperature

Backing: Polyester Film

notes: POF=Pop Off Foam, FT=Foam Tear, FP=Foam Picking

### Typical Performance Characteristics (continued)

Backside 90° Peel Adhesion		Substrate
5.1 N/cm	47 oz/in	Aluminum
5.3 N/cm	48 oz/in	Stainless Steel
4.7 N/cm	43 oz/in	Polypropylene (PP)
5.5 N/cm	50 oz/in	ABS

Property: Backside 90° Peel Adhesion  
 Method: ASTM D3330  
 Dwell/Cure Time: 72 hr @ Room Temperature  
 Backing: Aluminum Foil

### Available Sizes

Property	Values	
Note	Subject to Minimum Order Requirements	
Standard Roll Length	230 m	251 yd
Available Width	1000, 1372, 1524 mm	39, 54, 60 in
Normal Slitting Tolerance	±0.8 mm	±1/32 in
Core Size (ID)	76.2 mm	3 in

### Environmental Performance

Temperature Resistance: The L1 adhesive family is usable for short periods (minutes, hours) at temperatures up to 200°F (93°C) and for intermittent longer periods of time (days, weeks) up to 150°F (66°C).

Lower Service Temperature: -40°F (-40°C)

Humidity Resistance: High humidity has minimal effect on adhesive performance. No significant reduction in bond strength is observed after exposure for 7 days at 90°F (32°C) and 90% relative humidity.

### Handling/Application Information

#### Application Techniques

Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application will assist the adhesive in developing intimate contact with the bonding surface.

To obtain optimum adhesion, the bonding surfaces must be clean, dry, and well unified. Some typical surface cleaning solvents are isopropyl alcohol or heptane.\*

Ideal tape application temperature range is 70°F to 100°F (21°C to 38°C). Initial tape application to surfaces at temperatures below 50°F (10°C) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

#### Storage and Shelf Life

Store in original cartons at 70°F (21°C) and 50% relative humidity.

If stored under proper conditions, product retains its performance and properties for 24 months from the date of manufacture.

#### Trademarks

3M is a trademark of 3M Company.

# 3M™ Scrim Reinforced Adhesive Transfer Tape L1 + RT

## References

### Safety Data Sheet (SDS)

[https://www.3m.com/3M/en\\_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en\\_US&co=ptn&q=L1+RT](https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=L1+RT)

## Family Group

	L1 + DCP	L1 + RT
Adhesive Thickness (mm)	0.097	0.081
Liner	74# DK	74# DK
Liner Thickness (mm)	0.103	0.103
Liner Color	White	White

## ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

## Information

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

